



PR-C101 QUICK FACTS:

- 300 dpi dye-sublimation printing technology
- Full color edge to edge printing
- Industry leading 24-bit continuous tone printing
- Media thickness 30 mil
- First ever rotating LCD panel to fit any office environment
- All-in-one ribbon cassette and cleaning assist roller unit
- Removable 100 cards feeder
- Extremely small footprint and light weight (14lbs)
- 2-year hands-free warranty
- USB 2.0 output
- Windows compatibility

Specifications

- Printing System:** Single-Sided 300dpi, 24-bit continuous tone printing, 16.7million colors
- Printing Method:** Thermal transfer dye-sublimation
- Print Media:** PVC or polyester cards with polished PVC finish
- Media Size:** CR-80: 3.375" x 2.125" / 85.6 x 54mm
- Media Thickness:** 30mil
- Print Area:** Single-Sided Edge-to-Edge
- Input Hopper:** 100 cards
- Exit hopper:** 30 cards
- Image Memory:** 16MB with parallel processing, four memory modes
- System Memory:** 2.25MB
- Display:** First ever rotating LCD 16 Character 2-line display shows printer status and diagnostic prompts
- Ribbon Types:** YMCK 250 prints, K 1250 prints, & BK/OP 250 prints
- * Print Speed:** YMCKO: less than 144 cards / hour
- Interface:** USB 2.0
- Dimensions:** 7" (h) x 9" (w) x 13" (d), 180MM x 329MM x 222MM
- Weight:** 14lbs. / 6.5 kg
- MTFB:** 20,000 prints
- Operating Temp:** 10 to 35°C, 35-85%RH/without condensing
- Power source:** AC power source AC100/240v 50/60Hz auto-switching
- Agency Listing:** UL: UL1950: UL1950-1993
CE Class B
FCC A & B
- Drivers:** Windows Compatible
- Warranty:** 2-Year Hotswap.

PR5300E Dual Sided Quick Specs®

Pr5300 Dual Sided ID Card Printer Preliminary Specifications:

- Specifications:**
- Printing system:** 300 dpi, 24-bit continuous tone printing up to 16.7 million colors
- Printing method:** Thermal transfer dye-sublimation 256-grayscale, 8 bit
- Print media:** PVC or polyester cards with polished PVC finish
- Media size:** CR-80: 3.375" x 2.125/85.6x54mm
- Media thickness:** .020" (20mil) to .050" (50mil) / .508mm to 1.72mm CR-79: 3.303"x2.051" / 83.9mm
- Print area:** Edge to edge
- Input hopper:** 100 cards
- Output hopper:** 100 cards
- Image memory:** 8 MB with parallel processing, four memory modes
- System memory:** 2.25 MB
- Display:** LCD 16 character 2-line display shows printer status and diagnostic prompts

- Print ribbons options:**
- Print speed:*** 134 cards per hour (YMCKO)
- Interface:** USB 2.0
- Dimensions:** 16.57" (h) x 10.66" (w) x 13.03" (d) / 421 x 271 x 331mm
- MTBF:** 100,000 cards
- Weight:** 26.6 lbs. / 13kg
- Operating temperature:** 65 to 80F / 18 to 27C
- Powersource:** AC 100/240v 50/60Hz auto-switching
- Agency listing:** UL/CE/FCC
- Power source:** AC
- Drivers:** Windows compatible
- Warranty:** 2-year return to depot service printer warranty, 1-year unlimited



Image Sales, Inc.
1559 Third Avenue
Walnut Creek, CA 94597
Phone: 925-932-1031
Toll Free: 1-800-444-1821
FAX: 925-932-0560
Web. www.imagesales.com



Warranty Upgrade provides a loaner printer with exact configuration by 2nd day shipping. 3 Year maximum renewal.
Service Agreement is 4 scheduled service calls per Yr. to Clean, Calibrate & Adjust Printer within our local service area.